







Vessel Specifications

Dimensions	
Length overall, m Length between perpendicular, m Breadth overall, m Hull height, m Displacement of the vessel unloaded, t Displacement of vessel fully loaded, t Estimated draft, m Light draft, m Deadweight, t Net Tonnage, t Gross tonnage, t	108,3 107 25,6 7 4355 8900 3,5 1,66 4545 3768 5370
Capacities	
Crew, person Potable Water, t Technical water, t Fuel capacity, t Oil, t Cargo carrying capacity, t Oil consumption, kg / h Fuel consumption, kg / h Endurance	25 163 98,5 381 28 2966 0,75 40 20

General Data

Port of registry / Call sign	Baku / 4JHN
5 11 61 1	T1 1.1

The vessel is designed for laying of underwater pipelines with a diameter of 219-813 mm to the depth of the Purpose of the Ship

or 219-813 mm to the depth of the sea up to 195 m.

Non self-propelled seagoing pipe laying ship with pontoon type hull, with a sloping deck on starboard side, with the conning room (rudder house) on starboard side at the middle part of the ship's hull and with detectable. Type of the Ship

on starboard side at the middle part of the ship's hull and with detachable (removable) stinger serving as support to pipeline when lowering it from the stern of the sloping deck to the bottom of the sea.

Azerbaijan

1975 / Shipyard "Gusto–Sidam",
Rotterdam, Netherlands.

KE (*) [1] R1

Flag Year bui**l**t / builder

Class

Machinery and Propulsion

4 x diesel generators, consisting of 8FAN240 type diesels with a capacity of 4 x 720.3 kW (4 x 980 BHP). One diesel generator consisting of generator and DAFDT-615 type diesel with a capacity of 66.15 kW (90 RHP) Auxiliary engines Diesel generators (90 BHP)

Anchor Handling Gear

8 anchors, each weighting 13,6t; 63 mm in diameter Single-drum type with a pulling force of 882.9 kN (90t) at a wire picking speed of 12 m / min, with electric power drive with a capacity of 300 kW at 1000rpm. Anchors Anchor wires Anchors winches

Cargo Handling & Special Equipment


Bridge cranes	4 x non-rotating cranes with a carrying capacity of 5x40t, with handling radius of 3.45m.
Slewing crane	1 x with a carrying capacity of 60t with overboard handling radius of 3.45m and over stern handling radius of 4,00m, with a rotation angle of 300 degrees.
Additional	1 x crawler caterpillar crane with a lifting capacity of 100t.
Stinger	3 sectional spatial form with a total length of 100m.
Pipe storage	593 pipes with a length of 12m.

Navigation & Communication Equipment


AD/QD R/st.FS-2570 – 1pcs; UQD R/st.FM-8800 – 2; UQD R/st.FM-8500 – 1pcs; R/buy McMurdo E3a – 1pcs; UQD R/st.McMurdo R1 – 3pcs; RI C/vr. McMurdo R19SART – 1pcs; RI C/vr. McMurdo S4SART – 1pcs; UAIS FA-100 – 1pcs, Kenwood TK-2107 – 1; Kenwood TK-2207 – 4pcs; R/st. ICOM IC-M31 – 3pcs; R/st. ICOM IC-M24 – 3pcs.




GA Specifications




MAIN DECK



TWEENDECK



TANKTOP















Address: 2, Neftchilar Avenue, AZ 1003, Baku, Azerbaijan Republic Phone: (+99412) 404 37 00 | Fax: (+99412) 404 38 00 Email: projects@asco.az | Web: www.asco.az

Direct Contacts:

Phone: (+99412) 404 37 15; (+99412) 404 37 40